




**SUBMINIATURE
DIP RELAYS**

2 Form C 150mW

HFD2



- 2 Form C contact
- High sensitivity 150 mW
- Fits standard 16 pin IC socket
- High switching capacity 60W,125VA
- Epoxy sealed for automatic wave soldering and cleaning
- Single side stable and latching type is available

■ **CONTACT DATA**

Arrangement	2 Form C	
Initial Contact Resistance Max. (at 10mA 6VDC)	50mΩ	
Contact Material	Silver alloy, gold clad	
Contact Rating (Res. Load)	2A,30VDC 1A 125VAC	
Max. switching voltage	220VDC,250VAC	
Max. switching current	5 A	
Max. switching power	60W,125VA	
UL/CUR rating	2A at 30 VDC Resistive 1A at 120VAC Resistive	
Expected Life min. operations	Mechanical	10 ⁸
	Electrical	1×10 ⁵ ops 2A 30VDC
		5×10 ⁵ ops 1A 30VDC

■ **SPECIFICATION**

Initial Insulation Resistance	1,000MΩ 500VDC	
Dielectric Strength Between coil and Contacts	1,500VAC, 1min(1coil)	
	1,000VAC,1min(2coil)	
Between open contacts	1,000VAC,1min	
Surge Voltage between Contacts and coil	1500VAC	
Operate time (at nomi. Vot.)	4ms	
Release time (at nomi. Vot.)	3ms	
Temperature rise (at nominal voltage)	Max. 65°C	
Shock Resistance	Functional	490m/s ²
	Destructive	980m/s ²
Vibration Resistance	196m/s ²	
Humidity	98% +40°C	
Ambient temperature	-40 to +85°C	
Termination	PCB	
Unit weight	Approx. 8g	
Construction	Sealed	

■ **ORDER DESIGNATION**

HFD2 / 012 — S L2

Coil Voltage	Sensitivity	Sort
3、 5、 6、 9、 12 15、 24、 48VDC	S: Sensitive	Nil: Single side stable
	M: Standard	L1: Latching 1 coil
		L2: Latching 2 coil

■ COIL TABLE

Single side stable Standard (200mW) 20°C

Order Number	Coil Voltage VDC	Pick-up Voltage VDC (max)	Drop-out Voltage VDC (min)	Coil Resist. Ω 10%	Max. allow Voltage VDC
003-M	3	2.3	0.3	45	6
005-M	5	3.8	0.5	125	10
006-M	6	4.5	0.6	180	12
009-M	9	6.8	0.9	405	18
012-M	12	9.0	1.2	720	24
015-M	15	11.3	1.5	1125	30
024-M	24	18.0	2.4	2880	48
048-M	48	36.0	4.8	11520	96

Single side stable Sensitive (150mW) 20°C

Order Number	Coil Voltage VDC	Pick-up Voltage VDC (max)	Drop-out Voltage VDC (min)	Coil resist. Ω 10%	Max. allow Voltage VDC
003-S	3	2.4	0.3	60	7.0
005-S	5	4.0	0.5	167	11.5
006-S	6	4.8	0.6	240	13.8
009-S	9	7.2	0.9	540	20.8
012-S	12	9.6	1.2	960	27.7
015-S	15	12.0	1.5	1500	34.6
024-S	24	19.2	2.4	3840	55.4

Latching (2 coil) standard (200mW) 20°C

Order Number	Coil Voltage VDC	Set, Reset Voltage VDC (max)	Coil Resist. Ω 10%	Max. allow Voltage VDC
003-M-L2	3	2.25	45	6
005-M-L2	5	3.75	125	10
006-M-L2	6	4.5	180	12
009-M-L2	9	6.75	375	18
012-M-L2	12	9.0	720	24
015-M-L2	15	11.25	1125	30
024-M-L2	24	18.0	2040	48

Latching (2 coil) sensitive (150mW) 20°C

Order Number	Coil Voltage VDC	Set, Reset Voltage VDC (max)	Coil Resist. Ω 10%	Max. allow Voltage VDC
005-S-L2	5	4.0	167	11.5
006-S-L2	6	4.8	240	13.8
009-S-L2	9	7.2	540	20.8
012-S-L2	12	9.6	960	27.7
015-S-L2	15	12.0	1500	34.6
024-S-L2	24	19.2	3840	55.4

Latching (1 coil) standard (100mW) 20°C

Order number	Coil Voltage VDC	Set, Reset Voltage VDC (max)	Coil resist. Ω 10%	Max. allow Voltage VDC
003-M-L1	3	2.25	90	8.4
005-M-L1	5	3.75	250	14
006-M-L1	6	4.5	360	17
009-M-L1	9	6.75	810	25
012-M-L1	12	9.0	1440	34

Latching (1 coil) sensitive (75mW) 20°C

Order number	Coil Voltage VDC	Set, Reset Voltage VDC (max)	Coil resist. Ω 10%	Max. allow Voltage VDC
005-S-L1	5	4.0	330	16
006-S-L1	6	4.8	480	19
009-S-L1	9	7.2	1080	29
012-S-L1	12	9.6	1920	39
015-S-L1	15	12.0	3000	43

015-M-L1	15	11.25	2220	42
024-M-L1	24	18.0	4000	56


024-S-L1	24	19.2	7680	78

HFD2


OUTLINE DIMENSIONS, WIRING DIAGRAM AND PC BOARD LAYOUT

Outline Dimensions

Single side stable or Latching (1 coil)




Latching (2 coil)




PC Board layout

Single side stable or Latching (1 coil)




Latching (2 coil)




Wiring diagram (bottom view)

Single side stable or Latching (1 coil)



Latching (2 coil)



For latching, diagram shows the "reset" position
 Energize terminals 1 and 16 to "set"
 Reverse energize terminals 1 and 16 to "reset"


Diagram shows the "reset" position
 Energize terminals 1 and 16 to "set"
 Energize terminals 2 and 15 to "reset"

■ TYPICAL CONTACT LIFE EXPECTANCY

voltage	Power	Number of operations	
		Resistive Load	Inductive Load $\cos\phi = 0.7$
50 mV	50 μ W	5×10^7	5×10^7
30 VDC	20 W	3×10^6	1×10^6
30 VDC	30 W	5×10^5	3×10^5
30 VDC	60 W	1×10^5	1.5×10^4
60 VDC	20 W	3×10^6	--
60 VDC	30 W	5×10^5	--
60 VDC	60 W	1×10^5	--
30 VAC	40 VA	3×10^6	1×10^6
30 VAC	80 VA	1×10^6	3×10^5
30 VAC	120 VA	1×10^5	1.5×10^4
60 VAC	40 VA	3×10^6	1×10^6
60 VAC	80 VA	1×10^6	3×10^5
60 VAC	120 VA	1×10^5	1.5×10^4
125 VAC	40 VA	3×10^6	1×10^6
125 VAC	80 VA	1×10^6	3×10^5
125 VAC	125 VA	1×10^5	1.5×10^4

■ USEFUL CURVES

Maximum switching power



Coil Temperature Rise

